

Stemau S.r.l.

Legal Head Office and Showroom Via Pieve Ligure, 15 00168 Rome Warehouse and Showroom Via Refrancore, 26 00166 Rome Factory Via Morsesco, 11 00166 Rome Phone 0039.06.45.50.22.60 - info@stemausn.it - www.semausrLii VAT 01814361000 - FiscalCode 07/78980588

WPC FLOOR LIFE COLLECTION

TECHNICAL DATA SHEET In compliance with the provisions of the law Legislative Decree no. 206/2005 Regulations for consumer information"

DESCRIPTION: DOUBLE SIDE PLANK (1 SMOOTH PROFILE AND 1 KNURLED PROFILE) WITH SIDE MILLING SYMME-TRICAL F/F. WPC/WOOD PLASTIC COMPOSITE LAVING: WITH CLIPS ON WOODEN OR AZUMINUM JOISTS AND/OR ON JACKS WITH ADJUSTABLE SUPPORT. **COMPOSITION:** POLYETHYLENE (35%), VINYL POLYMER (3%), POWDER WOODEN (50%), LUBRICANT (3%), PIGMENT (3.45%), STRENGTHENER CALCIUM CARBONATE (4.50%), ANTIOXIDANTS (0.50%), UV AB-SORBERS (0.15%), FUNGICIDES (0.40%) PACKAGE: 2 OR 4 PIECES PACKAGE WEIGHT: 20 OR 30 Kg **USE: IDEAL FOR OUTDOOR** ACCESSORIES FOR INSTALLATION AND LAYING MAINTENANCE: CLIPS, SCREWS, JOISTS, JACKS WITH SUPPORT ADJUSTABLE, CLOSING PROFILES, SPE-CIFIC DETERGENTS.

EUROPEAN STANDARDS: UNI EN 15534-1:20 MARKING: CE

WPC (WOOD PLASTIC COMPOSITE) is the ideal flooring for outdoors. In fact it is suitable for outdoor use and climatic stress (rain, sun, vind, etc.).

It is durable, ecological resistant to water, wear and salt, non-slip, suitable for covering all outdoor environments, does not require particular meintenance and has a long life.

It does not deform, not split, not crack, not warp, it is resistant to mould, fungi and insects and it is extremely resistant to UV rays. For all these characteristics it is suitable for paving terraces, gardens, balconies, courtyards, porches, swimming pool edges, walkways, platforms, parios, gazebos, SPAs, refreshment areas, piers and docks.

WPS (rigid thermophysic wood polymer) is a compound made up of polyethylene (35%), vinyl polymer (3%), powder wood (50%), lubricant (3%), pigment (3.45%), strengthener calcium carbonate (4.50%), antioxidants (0.50%), uv absorbers (0.15%), fungicideS (0.4%%).

It has a double-sided profile, that allows it to be installed on both the smooth side and the striped side.



Stemau S.r.l.

Legal Head Office and Showroom Via Pieve Ligure, 15 00168 Rome Warehouse and Showroom Via Refrancore, 26 00166 Rome Factory Via Morsesco, 41 00166 Rome Phone 0039.06.45.50.22.60 - info@stemausrl.it - www.stemausrl.it VAT 01814361000 - Fiscal Code 07/78980588

WPC FLOOR LIFE COLLECTION

Storage

The product must absolutely be stored with intact and closed packaging in covered and dry environments. **Laving**

For laying it is recommended to contact specialized and qualified personnel.

WPC can be laid on any stable and well-levelled substrate (concrete, sand, gravel, grass), where an adequate slope has been provided, that allows the regular flow of water.

Wooden or aluminum joists, on which the planks are screwed, can be fixed to the substrate, or to jacks with adjustable support, to allow the flooring to be level and to allow the passage of channels for the flow of water.

If WPC Floor is laid on turf, it is necessary to level the area to be paved and lay one or two layers of non-woven polyester fabric, to avoid grass regrowth.

The installation distance between the planks must be at least 3 mm, to guarantee stability and prevent meading from being dangerous.

Decors

Samples or photographic reproductions are intended as indicative and non-binding. Once exposed to sunlight, decor's colour may darken or lighten. Main decors: Brown, Cream, Grey, Teak.



Maintenance

The WPC does not require specific maintenance. It will be sufficient to wash the floor with water and a suitable detergent. However, it is recommended to use a protective treatment, at least once a year, to increase the water-repellent properties. For extraordinary maintenance it is recommended to contact expert and qualified personnel.

Disposal

The floor should not be thrown into the environment, but extrusted to public waste disposal systems.

Warnings

It is absolutely forbidden to use the product as a structural component or in environments/places other than those indicated, modify the product, use installation methods other than those indicated, use glues for fixing, use cleaning products other than those indicated. The Company cannot be held responsible in any case for accidents or damages resulting from inappropriate use of the product, as well as from non-compliance even partial of the safety regulations and intervention procedures.