

## **КОЛЛЕКЦИЯ TECNIC**

## ЕВРОПЕЙСКИЙ СТАНДАРТ

**REGULATION NORMA UNI EN 13489** 

 $\triangle$ НАТУР РУСТИК свободный КЛАСС КЛАСС МИКС 1

КЛАСС МИКС 2

СЕЛЕКТ











Face of the element			
ХАРАКТЕРИСТИКИ		$\triangle$	
Sound sapwood or heartwood*	Not permitted Not permitted	Permitted Permitted up to 50% of the face, if distribuited	Slight traces permitted Permitted
Knots**			
Sound and intergrown	Permitted if: diameter ≤2 mm if not grouped together***	Permitted if: diameter ≤5 mm if not grou- ped together***	
Unsound	Permitted if: diameter ≤1 mm if not grouped together***	Permitted if: diameter ≤2 mm if not grou- ped together***	All features permitted without limit to size or quantity if these do not impair the strength or the wearing quality of the parquet flooring
Checks	Not permitted	Not through going.  Permitted if the width ≤0,5% of the width of the element	
Bark pockets	Not permitted	Not permitted	1
Lightning shake	Not permitted	Not permitted	1
Slope of grain	Permitted, no limit	Permitted, no limit	1
Colour variation	Permitted. Slight traces of natural discoloration (mineral lines) permitted	Permitted	
Medullary ray	Permitted	Permitted	_
Biodeterioration	Not permitted	Not permitted	Not permitted, except blue stain and black ho- les

## Non-visible parts

All features permitted without limit to size or quantity if these do not impair the strength or the wearing quality of the wood flooring.

<sup>\*</sup> Sound sapwood or "heartwood" shall be chosen depending on the wood species concerned.

<sup>\*\*</sup> Cracks in knots and knot holes shall be filled.

<sup>\*\*\*</sup> Knots are grouped together if the distance separating them, measured from edge to edge, does not exceed 30 mm.